

bonshire® mix & fill (Original)

Product Description

Bonshire color mix fill is a high-solids content waterborne binder based on acrylic for the production of wood putty. Is an economical product, quick and easy to use with most types of all wood. bonshire mix & fill is to mix with fine sawdust or wood dust from the timber. This will treated which give natural coloration.

Features

- Fast drying
- Easy to apply-simply mix with fine sawdust
- Low consumption
- Low odor
- Suitable for all types of wood
- Balance natural coloring timber for all types of wood
- Low solvent content
- Waterborne yet anti-corrosive

Preparation

Before applying the color mix fill, make sure the floor must be cleaned, dry with dust, dirt, wax and grease removed. Stir well with a stick before use.

Application

First mix the bonshire color mix fill with fine and clean sawdust / wood dust to a smooth consistency. The finer the dusting sand, the easier it will be to trowel-fill the mass and there will also be a better adhesion in the joints. Apply the mixture across the whole floor using a stainless steel trowel and repeat the procedure if necessary. If gaps wider than 2mm sanding will be next day to allow the mix fill drying time.

Technical data

Solid Content: 39.5%

Mixing Ratio: 40-50 % wood dust to 50 % color mix fill (gaps wider than 2 mm)
20-30 % wood dust to 80 % color mix fill (gaps wider less 2 mm)

Application Tool: Stainless steel trowel

Application Rate: 18-22 m²/Liter depending on size and quantity of gaps.

Drying time: 45-60 minutes depending on the width of the joint.

Shelf life: Shelf life 12 months in unopened container

Packing Size: 4kg

Our information based on laboratory tests and practical experience and may as such be considered a guide in connection with choice of product and working method. As the users working conditions is beyond our control, we do not assume any responsibility for the result. Our responsibility covers exclusively personal injury or damage to property which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

KSC INDUSTRIES (M) SDN BHD No16, Jalan Sungai Jeluh 32/189, Bukit Naga Seksyen 32 ,40460 Shah Alam selangor.
Tel:(03)-51668790 Fax: (03)-51670942 Website:www.ksc-monatec.com Email: info@ksc-monatec.com.