

bonshire® waterborne acrylic finish

e-3

acrylic top & primer

e
a
s
y
f
i
n
i
s
h

Product Introduction

bonshire top & primer e-3 is an waterborne acrylic base that suitable for timber flooring & other wooden application.

Features

- *Odorless
- *Easy to apply and clear
- *High resistance wear.
- *No-bubbling, beautiful leveling.
- *Fast drying
- *Excellent durability
- *Non-yellowing

Preparation

When you using the bonshire acrylic top & primer you must make sure floor surface must be cleaned, dry with dust, dirt, wax and grease removed. Shake well before use.

Technical Data

Solid content	33%
Application Tools	floor coater, 10-inch trowel, roller
Suitable use	kitchens, living rooms, active homes with children, office, hospital, shop,etc
Dry Time	2-3 hours for one coat (if to encounter air temperature is below 28°C dry time is not stable)
shelf-Life	Shelf life 12 months in opened container.
Gloss level	gloss 20, matt 80%.
Coverage	1200-1400 square feet / 10 kg
Storage	Store away from direct sunlight.
Package size	GW10 kg
Technology	German
Material	German



Our information based on laboratory tests and practical experience and may as such be considered a guide in connection with choice of product and working method. As the users working conditions is beyond our control, we do not assume any responsibility for the result. Our responsibility covers exclusively personal injury or damage to property which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

KSC INDUSTRIES (M) SDN BHD No16, Jalan Sungai Jeluh 32/189, Bukit Naga Seksyen 32, 40460 Shah Alam selangor.
Tel:(03)-51668790 Fax: (03)-51670942 Website:www.ksc-monatec.com Email: info@ksc-monatec.com.